TECHNICAL SHEET AUTOMOBILE & CYCLES





Ref: A02308 CHAIN GREASE 75ML PUCK

For lubricating and maintaining bicycle grease.

- √ High stability
- ✓ Exceptional adhesive properties
- ✓ Anti-corrosion protection
- ✓ Resists wear and high pressure

SPECIFICATIONS

Dropping point: >160°C	Colour: green
Density: 0.83 +/- 0.2	Properties: Grade NLGI 2
Soap: Lithium/Calcium	Odour: Solvent

APPLICATION

No modification to joints.

- High stability preserves greasy texture when in use.
- Remarkable adhesion resistance to water (washing)
- Excellent adherence to metal in a range of conditions: heavy rain, dust, high temperatures, etc.
- High-performance protection against corrosion (EMCOR test) for prolonged use in damp conditions.
- Highly resistant to wear and extreme pressure

For lubricating chains, ball bearings, shafts, axles and other small components.

RECOMMENDED FOR

- Bicycles: maintaining cables, derailleurs, etc.
- Garages
- Bike hire
- Sports stores
- Gyms
- Farming, marine, forestry, civil works

INSTRUCTIONS FOR USE

Removes persistent grease from parts.
Shake can. Hold the can upright.

Spray on surfaces to be greased from 20 cm.

We recommend using this product once a month to remove residual grease before reapplying grease.

PACKAGING

<u>Presentation:</u> Aerosol 75ml <u>Pack size:</u> Carton of 24

Aluminium can Diameter: 35mm Height: 125mm Nominal volume:: 110 ml/Net volume: 75 ml Pallet size: 4608 units – 192 cartons

REGULATIONS

FOR INDIVIDUAL AND PROFESSIONAL USE

Dangerous. Follow precautions for use.

Refer to the safety data sheet (SDS). Available on request.

Our data sheets are prepared with current knowledge and subject to modifications. Photo nonbinding

07/11/2018 Index 3.1



